

This certificate is granted and awarded by the authority of the Nadcap Management Council to:

CTL Aerospace

5616 Spellmire Dr Cincinnati, OH 45246 United States

This certificate demonstrates conformance and recognition of accreditation for specific services, as listed in www.eAuditNet.com on the Qualified Manufacturer's List (QML), to the revision in effect at the time of the audit for:

Composites

Certificate Number: 6001218264 Expiration Date: 31 May 2025 Accreditation Length: 18 Months

Jay Solomond

Executive Vice President & Chief Operating Officer



SCOPE OF ACCREDITATION

Composites

CTL Aerospace 5616 Spellmire Dr Cincinnati, OH 45246

This certificate expiration is updated based on periodic audits. The current expiration date and scope of accreditation are listed at: www.eAuditNet.com - Online QML (Qualified Manufacturer Listing).

In recognition of the successful completion of the PRI evaluation process, accreditation is granted to this facility to perform the following:

AC7000 Rev A - AUDIT CRITERIA FOR NADCAP ACCREDITATION

AC7118 Rev I - Nadcap Audit Criteria for Composites (to be used on audits on/AFTER 31-Dec-2023)

- 14.2 NC Ply Cutting (Applies to CP, KSP, LRP, MB or PAR)
- 15.1.5 or 15.1.6 Complex Core Processing (Applies to CP only)
- 18.1 and 2 Resin Preparation and Mixing (Applies to LRP Only)
- 19.1 and 2 Liquid Resin Infusion (Applies to LRP Only)
- 21.1 Autoclave (Applies to LRP, MB or PAR)
- 21.2 or 3 or 4 Oven (Applies to CMP, LRP, MB or PAR)
- 21.5 and 6 Press (Applies to LRP, MB or PAR)
- 22.2 NC Machining/Trimming/Drilling (Applies to CMP, LRP, MB or PAR)
- 23 Miscellaneous Bonding (Applies to CMP, LRP, MB or PAR)
- 24.1 or 2 or 3 Process Control Testing (AC7118) or AC7122–P (Applies to CP, CMP, LRP, MB or PAR)
- CMP Compression Molding
- CP Core Processing
- LRP Liquid Resin Processing
- MB Metal Bond
- PAR Prepreg/Adhesive Bonding/Resin Film Infusion

AC7122/1 Rev B - Nadcap Audit Criteria for Non Metallic Materials Testing – Mechanical

Testing

- 1.1.1 Tensile Ambient Temperature
- 1.1.2 Tensile Non-ambient Temperature
- 1.1.3 Tensile Strain Measurement
- 1.10.1 T-Peel
- 1.12.1 Climbing Drum Peel
- 1.13.1 Floating Roller Peel

t-frm-0004 29-May-20

- 1.2.1 Compression Ambient Temperature
- 1.2.2 Compression Non-ambient Temperature
- 1.2.3 Compression Strain Measurement
- 1.21.1 Flatwise tension, Sandwich
- 1.22.1 Sandwich Flexure
- 1.3.1 Shear Ambient Temperature by SBS
- 1.3.2 Shear Ambient Temperature ±45 Tension
- 1.3.5 Shear Non-ambient (any method)
- 1.3.6 Shear Strain Measurement
- 1.4.1 Flexural Ambient Temp
- 1.4.2 Flexural Non-ambient
- 1.4.3 Flexural Strain measurement
- 1.9.1 Single Lap Shear Ambient Temperature
- 1.9.2 Single Lap Shear Non–ambient Temperature

AC7122/2 Rev A - Nadcap Audit Criteria for Non Metallic Materials Testing – Physical Testing

- 2.1.2 Hardness Testing: Barcol
- 2.1.3 Hardness Testing:Durometer
- 2.2.1 Density/ Specific Gravity
- 2.3.2 Resin/Fiber /Void Content by: Burn off
- 2.3.3 Resin/Fiber /Void Content by: Solvent wash
- 2.5.1 Volatile Content
- 2.6.1 Gel Time
- 2.7.1 Flow
- 2.8.1 Fiber Areal Weight
- 2.8.2 Prepreg Areal/Adhesive Film Weight

AC7122-P Rev B - Nadcap Audit Criteria for Non Metallic Materials Testing – Laboratories P - Part Manufacturers Captive LaboratoriesPart manufacturer's captive testing laboratories (Only in conjunction with AC7118

Class A: Composites

Class B: Adhesive/Adhesive Primer

t-frm-0004 29-May-20